



Liftsales@Tempemobility.com

GMC Savana 1997-2022 FMVSS (US)

Vehicle Year	Customer Name / Job Reference	Dealership Sales Person
Date	Dealership ID# or Name & Location	For Tempe Use Only

VAN MODEL	
Passenger	OEM seating behind front seats / interior panels/ flooring
Cargo / Commercial	Empty interior behind front seats
Conversion / RV	Non-standard OEM components added. Component removal probable

LIFT LOCATION	
Side Door	Private Use lift
Rear Door	Private Use lift - Bumper modification required
Rear Door	Commercial lift - Requires 56" minimum door height

DOOR OPENING HEIGHT	
Standard	Side 47.9" / Rear 49.4"
Raised	Clear door opening height and width confirmation required
Lowered Floor	Drop opening width and opening height confirmation required

INSTALLATION KIT		CAPACITY
SIDE		
RI-11100	1997-2005 Fixed Support	600
RI-58332	2005 + Adjustable Support	800
Not Applicable	Dealer Provided Solution	-
REAR		
RI-13340	1997-2018	800
Not Applicable	Dealer Provided Solution	-

Special Notes

GMC Savana 1997-2022 FMVSS (US)

MODEL / PART NUMBER	DESCRIPTION	CAPACITY
SIDE – STANDARD DOOR		
RELIANT		
S1200-G00101000	30X44 Platform, Solid	600 / 800
S1204-G00100100	32X44 Platform, Solid	600 / 800
CLEARWAY		
S1231-G00100100	30X42 Platform, Vertical Split	600 / 800
KLEARVUE		
K1203-G10100100	30X51 Platform, Bi-Fold	600 / 800
K1205-G10100100	32X51 Platform, Bi-Fold	600 / 800
SLIDE-AWAY		
ST00-VG000010AG	30X42 Platform, Sliding	600
UNI-LITE - ELECTRIC / ALUMINUM		
UL2806-2G01000	29X40 Platform, Solid	600
UL2810-2G01000	32X40 Platform, Solid	600
REAR – STANDARD DOOR (BUMPER MODIFICATION REQUIRED)		
RELIANT		
S1200-G00101000	30X44 Platform, Solid	600
S1204-G00100100	32X44 Platform, Solid	600
CLEARWAY		
S1231-G00100100	30X42 Platform, Vertical Split	600
KLEARVUE		
K1203-G10100100	30X51 Platform, Bi-Fold	600
K1205-G10100100	32X51 Platform, Bi-Fold	600
SIDE / REAR – RAISED DOOR / LOWER FLOOR		
Contact Tempe Technical Sales		

DOOR OPERATORS*	Interlock / Remote Systems Required
RI-RDO2908	Side - Swing - Non Latching
RI-RDO2502	Side - Slide - Non Latching
RI-RDO2911	Rear - Non Latching
Not Applicable	

*Non-Latching Doors Must Be Used In Conjunction With A Solid Platform

WIRELESS REMOTE	
M5100	Remote with (2) Wireless Key Fobs
M5200	Internal Switches (Dash Station), Rear Tail Light Magnetic Switches
Not Applicable	



Liftsales@Tempemobility.com